

B100PROX-MF-SA

STANDALONE BIOMETRIC READER WITH
MIFARE CARD READER

B100PROX-MF-SA is a simple one-door standalone biometric and RFID system (or 2 doors when used with DINRTT or RU2). The reader programming is quick and easy. It can store up to 98 fingerprints and 2000 RFID cards. It has one integrated relay output and one exit button input. If secure installation is needed, the reader can be connected to a remote relay unit in a secured area. Complete setup and programming can be done by swiping. It can read Mifare Classic, Ultralight and Desfire.



bx Black Edition
Product available in Black ABS

FEATURES

- Power supply: 9-14 VDC, 150 mA
- Capacity: 98 Fingerprints and 2000 Cards
- Output: One relay NO/NC contacts
- Output maximum current: 2A, 24 VAC/VDC
- Push button input: Yes
- Door time: Pulse (1-30 s) or Toggle (ON/OFF)
- Entry mode: Finger or Card
- Sensor: Swipe capacitive
- Card reader mode: Mifare Classic, Ultralight, Desfire
- Read range: 1.5-5.5 cm
- Programming: By swiping
- Admin/Installer fingers: 1 Admin and 1 Installer finger
- Backlight ON/OFF: Yes
- Buzzer ON/OFF: Yes
- Indication: Tricolor Status LED
- Mounting: Surface mount
- IP factor: IP54 (internal use only)
- Operating temperature: 0°C to +50°C, non condensing

Compatible devices: RTT, DINRTT, RU2


FOBS & CARDS




Ref.	PBX-1E-MS50	PBX-2-MS50	PBX-2C-MS50
Features	ABS 13.56MHz tags (1K)	ISO Card 0.75mm - 13.56MHz (1K)	NISO Card 2mm - 13.56MHz (1K)

Ref.	PBX-2-MS70
Features	ISO Card 0.75mm - 13.56MHz(4K)

DIMENSIONS



VERSIONS



B100PROXBK-MF-SA
Black - ABS



B100PROXS-MF-SA
Silver - ABS

LEDS



Access Granted



Idle Mode



Access Denied

Tricolor Indication uni-LED

WITH REMOTE RELAY AT SECURED AREA

