




Elegant and compact 125 kHz RFID reader. The housing comes with a big rectangular LED. Designed to be installed either outside or inside, it has a RS-485 bus. Its tricolor LED, tamper and buzzer are managed directly by the WS4 controllers. It can read EM or HID 125 kHz cards, depending on the programming selected.

— FEATURES ______

- Surface mount
- Housing: ABS (black or silver)
- Indoor/outdoor use
- RFID reader compatible EM 4002/4100 and HID (125 kHz)
- Reading distance: up to 5 cm
- RS-485 output
- Audible and visual feedback
- Green and Red Led: managed by the host *
- Orange LED: idle backlight (ON/OFF)
- 1 internal buzzer (ON/OFF), managed by the host
- Tamper protection: when opened or dismantled
- Voltage: 9 14V DC
- Current Consumption: max 50 mA
- IP 65
- Operating temperature: -20°C to +50°C
- Operating humidity: 5% to 95% RH without condensation

- TRICOLOR LED STATUS –





Green LED Orange LED Access Granted

Red LED Idle Mode Access Denied

FOBS & CARDS



With red, green and orange LEDs, managed by the host



WS4

00


Ref: MTPXBK-RS-EH Black - ABS

RS-485

* Compatible only with our

WS4 controllers

Ref: MTPXS-RS-EH Silver - ABS



MTPX-RS-EH DS EN Ve1



VERSIONS

