MTPADP-RS-MF

KFYPAD AND MIFARF RFID RFADFR WITH RS-485 OUTPUT

This double technology reader offers a double access security, including a keypad and a compact 13.56 MHz reader. It can be installed either outside or inside. It comes with a RS485 bus and a backlight keypad. Its LEDs, tamper and buzzer are managed directly by the WS4. It can read Mifare Classic, Desfire and Ultralight.

- FFATURES --

- Surface mount
- ABS housing
- Colour: Black or silver
- Technology: Keypad + Mifare RFID (13.56 MHz)
- Keys: Backlit metallic
- Reader type: Mifare Classic, Desfire and Ultralight cards
- Read range: up to 5 cm
- RS-485 output
- Green and red LEDs managed by the host *
- 1 internal buzzer (ON/OFF), managed by the host
- Tamper protection: when opened or dismantled
- Push buttons: 1
- Voltage: 9 14 V DC
- Current Consumption: 30 mA stand-by; 100 mA maximum.

MECHANICAL CARACTERISTICS

- IP rating: IP 65
- Operating temperature: -20°C to +50°C
- Operating humidity: 5% to 95% RH without condensation
- Weight: ~0.17 kg

DIMENSIONS & COLOURS













Backlit keypad

The MTPADP-RS-MF is equipped with an orange backlight that can be easily disabled if necessary with My WS4. The keypad changes its backlight color when the code or card is presented.







Green backlight Access granted

Orange backlight Iddle mode

Red backlight Access denied

FOBS & CARDS







Ref. **Features**

PBX-1E-MS50 ABS Keyfob 13.56MHz

PBX-2-MS50 0.75mm ISO Card -

13.56MHz

PBX-2C-MS50 2mm NISO Card -13.56MHz



